





Prism Data Cabinets have been manufacturing high quality enclosures for the communications industry since 1997 and we like to think our substantial growth as a company in the subsequent five years – the publication of this new catalogue coincides with our second premises-move in the same period – is testament to the quality of our products and our commitment in all areas of customer service.

While this catalogue announces the availability of our new FI Server Cabinet Range, demand for our standard enclosures continues unabated and they can be found in such prestigious establishments as Government Foreign & Commonwealth Offices worldwide, the BT Tower, Madame Tussauds, the Lotus and Mercedes Benz headquarters, Comet stores nationwide and The Wimbledon Lawn Tennis Club.

We believe our considerable, fast-growing and varied customer base is an indication of the success of our self-appointed targets as regards the customers' needs and requirements. Our sales teams' guiding light is that no query is too small and no job too big.

We are committed to next-day delivery of stock items and those products we do not deliver on our own fleet of custom-made vans are subject to internet-tracking. Furthermore, proof of delivery can be faxed to you, if required, and our level of customer service even extends to the availability of on-site assembly by our team of drivers and engineers.

New product range


To complement the existing range our in-house team of engineers have designed the FI Server Cabinet, a high-tech, new design of enclosure which we believe offers a whole host of advantages to all those involved in the data installation chain.

Its' unique, modern and inventive design serves proof of our ongoing commitment to the upgrading of our product range and allied to the high levels of customer service and product awareness mentioned above, we believe Prism Data Cabinets is best served to cater for any and all customers' needs in the communications sector.

	Free standing cabinets	page
FI	Server cabinet range	2-3
FI	19" free standing 600mm wide	4
FI	19" free standing 800mm wide	
PI	Data cabinet range	6-7
PI	19" free standing 600mm wide	8
PI	19" free standing 800mm wide	
	Wall boxes	10
FI	Wall boxes	1
FI	19" two section 600mm wide x 550mm deep	1
FI	19" 700mm wide x 500mm deep	1
PI	Wall boxes	12
PI	19" 600mm wide x 450mm deep	12
PI	19" 700mm wide x 500mm deep	12
PI	19" two section 600mm wide × 550mm deep	12
	Accessories	13
	Shelves	4
	Fixed Telescopic	4
	Cantilever	4
	Special Shelves	4
	Rotating keyboard shelf	4
	Cable Tray	4
	Fans	15
	Roof mounted Rack mounted	15
	Plinth	15
	Door conversion kit	15
	Castors and feet	15
	Baying kits	16
	Power distribution units	16
	Blank panels	16
	Brush Strip Panel	16
	Cable management bars	16
	Jumper rings	16
		1

Server cabinet range
























Designed by our in-house team of engineers, the FI server cabinet range provides ease of commissioning, cable-routing and maintenance. The unique box-section folding technique on the front and rear doors ensure extra strength and rigidity. Furthermore, an attractive and modern looking exterior ensures it will fit well in any office environment.

FI Server cabinet range

Design features

Construction

I Extruded polished aluminium chassis providing high load capacity

- 2 180° door opening
- 3 Removable side panels, slide mechanism
- 4 Quick release doors
- 5 Large floor aperture

Visibility

- 6 Safety glass door
- 7 Vented rear door

Equipment installation

8 'U' height position markers for accurate equipment positioning. Due to their unique design all major server manufacturers products can be fitted

Thermal management

- 9 Ventilated front door and rear door
- 10 Roof mounted fan may be retro fitted without disturbing installation

Security

II Slam-latch lock, secures front door and rear door. Camlocks secure side panels

Finish

• Stove enamelled Graphite grey

Accessories

See pages 13-16

The FI server cabinet is available with two door styles. The standard doors are shown on pages 4+5, whilst the doors illustrated here are an alternative option.

3

Free standing cabinets

19" 600mm wide

- Size range: 27, 42, and 45u
- Available in 900 or 1000mm deep

Standard FI Server Cabinet consists of:

- · Aluminium frame construction cladded with metal front and rear doors and lift off panels
- I x enclosed smoked glass front door with punched-vented surround (Includes a heavy-duty slam-latch lock)
- I x lockable rear swing door with punched-vented surround
- 2 x lockable metal lift-off panels
- I x vented top cover (can house up to 10 fans)
- 4 x transport castors Please note that for ease of transport, assembled cabinets are delivered on standard castors. However, we do not recommend them for installation purposes.
- 4 x adjustable 19" universal-style profiles fitted front and rear
- 2 x adjustable mid-style profiles
- Stove enamelled Graphite grey finish

Options

The cabinet shown is standard. The different style aluminium punched insert front and rear doors shown on pages 2+3 are available on request, for an extra premium.

Ordering information

600mm wide x 900mm deep

product code	depth mm	height mm	width mm	
FI-CAB2769	900	1410	600	27U
FI-CAB4269	900	2075	600	42U
FI-CAB4569	900	2210	600	45U

600mm wide \times 1000mm deep

product code	depth mm	height mm	width	
FI-CAB2761	1000	1410	600	27U
FI-CAB4261	1000	2075	600	42U
FI-CAB4561	1000	2210	600	45U



19" 800mm wide





- Size range: 27, 42, and 45u
- Available in 900 or 1000mm deep

Standard FI Server Cabinet consists of:

- Aluminium frame construction cladded with metal front and rear doors, and lift off panels
- I x enclosed smoked glass front door with punched-vented surround (Includes a heavy-duty slam-latch lock)
- I x lockable rear swing door with punched-vented surround
- 2 x lockable metal lift-off panels
- I x vented top cover (can house up to 10 fans)
- 4 x transport castors
 Please note that for ease of transport,
 assembled cabinets are delivered on standard
 castors. However, we do not recommend
 them for installation purposes.
- 4 x adjustable 19" universal-style profiles fitted front and rear (cable management can be fitted to front if required)
- 2 x adjustable mid-style profiles
- Stove enamelled Graphite grey finish

Options

The cabinet shown is standard. The different style aluminium punched insert front and rear doors shown on pages 2+3 are available on request, for an extra premium.

Ordering information

800mm wide x 900mm deep

product code	depth mm	height mm	width mm	
FI-CAB2789	900	1410	800	27U
FI-CAB4289	900	2075	800	42U
FI-CAB4589	900	2210	800	45U

800mm wide x 1000mm deep

produc code	depth mm	height mm	width mm	
FI-CAB278	1000	1410	800	27U
FI-CAB428	1000	2075	800	42U
FI-CAB458	1000	2210	800	45U

Data cabinet range
























PI Our original data cabinet range has become a popular selling unit over the years because it meets the all-round, standard requirements of data installation — ease of assembly and access, safety and security in use, and its' durability once assembled. In short, as good as value-for-money data cabinet that is available on the market today.

Design features

I Construction
Steel frame chassis with a considerable load capacity

Access

- 2 Swing front door opening
- 3 Removable side panels
- 4 Large floor aperture
- 5 Quick release door pins

Visibility

6 Smoked glass front door

Equipment installation

7 'U' height position markers for accurate equipment positioning (cable management fitted to front of 800mm wide cabinets)

Thermal management

8 Ventilated side panels and rear door See Options and Accessories below for additional thermal management alternatives

Security

9 Slam-latch front door lock (side and back panels also lockable)

Finish

Stove enamelled Goose grey Other colours may be available on request, at additional cost

Options and Accessories

- 10 Roof mounted fan
- II Rack mounted fan
- 12 Plinth

See pages 13-16 for comprehensive list and explanation of usage

Free standing cabinets

19" 600mm wide

- Size range: 18, 27, 39, 42 and 45u other sizes may be available on request
- Available in 600 or 800mm deep
- Standard colour finish is stove enamelled Goose grey (other colours may be available on request, i.e. Graphite grey finish on page 6)

Standard data cabinet consists of:

- I x enclosed glass front door with slam-latch lock
- 2 x lockable side panels
- I x rear swing door
- I x vented top cover
- 4 x 19" adjustable profiles
- 4 x transport castors
 Please note that for ease of transport,
 assembled cabinets are delivered on standard
 castors. However, we do not recommend
 them for installation purposes.

Ordering information 600mm wide x 600mm deep

product code	weight kg	depth mm	height mm	width mm	
CAB1866	50	600	990	600	18U
CAB2766	70	600	1360	600	27U
CAB3966	90	600	1930	600	39U
CAB4266	95	600	2070	600	42U
CAB4566	105	600	2205	600	45U

600mm wide x 800mm deep

product code	weight kg	depth mm	height mm	width mm	
CAB1868	55	800	990	600	18U
CAB2768	75	800	1360	600	27U
CAB3968	95	800	1930	600	39U
CAB4268	110	800	2070	600	42U
CAB4568	120	800	2205	600	45U







- Size range: 27, 39, 42 and 45u other sizes may be available on request
- Available in 600mm or 800mm deep
- Standard colour finish is stove enamelled Goose grey
- Standard components are the same as for the 600mm wide range opposite, but the 800mm wide unit comes with cable management attached to the front profiles

• Options

The 800mm cabinet inset illustrates some of the alterations that can be made to the standard cabinet. For example, the cabinet shown is Graphite grey and boasts aluminumpunched inserts on the side panels and rear door. Lead times will vary on non-standard items.

Ordering information

800mm wide x 600mm deep

product code	weight kg	depth mm	height mm	width mm	
CAB2786	85	600	1360	800	27U
CAB3986	120	600	1930	800	39U
CAB4286	130	600	2070	800	42U
CAB4586	135	600	2205	800	45U

800mm wide x 800mm deep

product code	weight kg	depth mm	height mm	width mm	
CAB2788	90	800	1360	800	27U
CAB3988	130	800	1930	800	39U
CAB4288	135	800	2070	800	42U
CAB4588	140	800	2205	800	45U













Wall boxes

600mm wide 2 section



- Size range: 6, 9, 12, 15 and 18u
- 600mm wide x 550mm deep (detachable rear section 100mm deep; front section 450mm deep)
- Earth bonding kit supplied (as with all wall boxes)
- Stove enamelled Graphite grey finish

Additional features include:

- Lift off hinges connecting front and rear sections
- Lockable perspex front door
- Two adjustable 19" profiles to enable equipment/shelving positioning (see accessories page 13-16)
- Brush-strip cut-out on top and bottom of wall box

Ordering information

product code	weight kg	depth mm	height mm	width mm	
FI-WB6SB	15	550	335	600	6U
FI-WB9SB	17	550	470	600	9U
FI-WB12SB	20	550	605	600	12U
FI-WB15SB	23	550	740	600	15U
FI-WB18SB	26	550	870	600	18U











700mm wide



- Size range: 9, 12, 15 and 18u
- 700mm wide x 500mm deep
- Stove enamelled Graphite grey finish
 Additional features include:
- Slam-latch lock on front door
- Quick release swing doors on side and rear to enable easy all-round access
- Cable management panels fitted to profiles
- Brush-strip cut out on top and bottom of wall box

weight kg	depth mm	height mm	width mm	
17	500	470	700	9U
20	500	605	700	12U
23	500	740	700	15U
26	500	870	700	18U
	17 20 23	500 17 500 20 500 23	mm mm kg 470 500 17 605 500 20 740 500 23	mm mm mm kg 700 470 500 17 700 605 500 20 700 740 500 23



600mm wide

- Size range: 6, 9, 12, 15 and 18u
- 600mm wide × 450mm deep
- All of the PI wall boxes have the following features as a minimum:
- · Welded construction
- Lockable perspex front door in a steel surround (over 90° door opening with quick release pins)
- 2×19 " uprights at front
- · Access holes with gland plates top and bottom
- · Vented side panels
- · Earth bonding kit
- Stove enamelled Goose grey finish (colour options at additional cost)

Ordering information

	width mm	height mm	depth mm	weight kg	product code
6U	600	335	450	12	WB6
9U	600	470	450	14	WB9
I2U	600	605	450	16	WB12
15U	600	740	450	18	WB15
18U	600	870	450	20	WB18



700mm wide

- Size range: 9, 12, 15 and 18u
- 700mm wide x 500mm deep

Additional features

- Slam-latch lock on front door
- Quick release swing doors on side and rear to enable easy all-round access
- Cable management panels fitted to profiles

Ordering information

product code	weight kg	depth mm	height mm	width mm	
WB9/SD	17	500	470	700	9U
WB12/SD	20	500	605	700	12U
WB15/SD	23	500	740	700	15U
WB18/SD	26	500	870	700	18U



600mm wide 2 section

- Size range: 6, 9, 12, 15 and 18u
- 600mm wide x 550mm deep (detachable rear section 100mm deep; front section 450mm deep)

Additional features include:

- Lift off hinges connecting front and rear sections
- Lockable perspex front door
- Two adjustable 19" profiles to enable equipment/shelving positioning (see accessories page 13-16)

product code	weight kg	depth mm	height mm	width mm	
WB6/SB	15	550	335	600	6U
WB9/SB	17	550	470	600	9U
WB12/SB	20	550	605	600	12U
WB15/SB	23	550	740	600	15U
WB18/SB	26	550	870	600	18U





















Shelves

Fixed



- Fixed between 19" mounting posts
- Vented
- Standard depths 450mm & 570mm, width 465mm

Ordering information

product code	depth mm	width mm
SHE450	450	465
SHE570	570	465

Telescopic




- Fixed between 19" mounting posts
- 450mm & 570mm standard depths

Ordering information

product	depth	width
code	mm	mm
SHE450-TEL	450	465
SHE570-TEL	570	465

Cantilever



Sizes available: $1u \times 200$, $1u \times 300$, $2u \times 400$

- Fix to front mounting posts
- Vented
- Ideal for wallboxes

Ordering information

product	depth	width	
code	mm	mm	size
SHE200/IFM	200	465	lu
SHE300/1FM	300	465	lu
SHE400/2FM	400	465	2u

Rotating keyboard shelf



 Ideal for housing standard keyboards, which are larger than the 19" aperture.
 Also includes pull out mouse tray

Ordering information

product code	depth mm	size
SHEKEY	450	lu

Cable trays



Size range: 27u, 39u, 42u, 45u

- Widths available 100mm, 150mm and 300mm
- Stove enamelled Goose grey finish
- Other sizes/widths may be available on request

Ordering information

size	width 100mm code	I 50mm code	300mm code
27u	CT27100	CT27150	CT27300
39u	CT39100	CT39150	CT39300
42u	CT42100	CT42150	CT42300
45u	CT45100	CT45150	CT45300

Special shelves

Please contact us with details of your particular requirements for special shelving.

Fans

Roof mounted fan unit



- Fitted with 4 fans or 2 fans on data cabinet range (6 way fans available on FI server range)
- Quiet fans (27db) are fitted as standard
- High Speed fans are available for increased heat dispersion

Ordering information

product code
FAN2RM
FAN4RM
FAN6RM

Rack mounted fan unit




- Iu Height
- 2 4 Fans
- Fitted with quiet fans (27db) as standard
- High Speed fans are available for increased heat dispersion
- Smaller units (2 3 fans) are ideal for wall boxes

Ordering information

description	product code
2 Way	FAN2RK
3 Way	FAN3RK
4 Way	FAN4RK

Plinth



- Four Size Options
- Welded construction
- Gland plates on side and rear, 100mm high

Ordering information

product code	depth mm	height mm	width mm
PLINTH66-100	600	100	600
PLINTH68-100	800	100	600
PLINTH86-100	600	100	800
PLINTH88-100	800	100	800

Door conversion kit



- Fits beneath or above any door
- Provides access for cable and surface wiring applications

Ordering information

product code	width mm	size
PAN3U600	600	3u
PAN3U800	800	3u

Castors and feet



- Heavy Duty Castors supplied in sets of four (2 locking, 2 non-locking)
- Adjustable feet are supplied in sets of four

description	product code
Set of four heavy duty castors	CASTOR-HD
Set of four adjustable feet	FEET-SET

Baying kit



• Baying Kits are used to join cabinets together

Please note that side panels must be removed in order to bay the cabinets together.

Ordering information

description	product cod
Baying Kit	BAYKIT0

Power unit



- Vertical PDU sizes available are 4, 5, 6, 8, 10, 12 way
- Horizontal PDU sizes available are 4, 5, 6 way Please note that a wide range of 'special' units are available eg. Filtered, European, USA, unswitched etc. Lead times may vary according to

Ordering information

	Vertical product code	Horizontal product code
4 Way	PDU4V	PDU4H
5 Way	PDU5V	PDU5H
6 Way	PDU6V	PDU6H
8 Way	PDU8V	
10 Way	PDU10V	
12 Way	PDU12V	

Blank panels



• Sizes: Lu, 2u, 3u, 4u

specification required.

- Mild Steel, rolled edge
- Larger sizes available to order

Ordering information

size	product code
lu	BLPLIU
2u	BLPL2U
3u	BLPL3U
4 u	BLPL4U

Brush strip panels



- · Sizes: Lu, 2u
- Mild Steel fitted with a brush strip
- Ideal for 600mm wide cabinets as additional cable management

Ordering information

size	product code
lu	BRUSHIU
2u	BRUSH2U

Cable management bars



Sizes IU & 2U

- 4 rings, radiused edges
- · Black finish

Ordering information

size			product code
	lu	4 Ring	CMB1U4
	2u	4 Ring	CMB2U4

Jumper rings



70mm x 70mm

- Designed to fit on cable management on 800 wide cabinets
- Stove enamelled Goose grey

65mm x 45mm

- Designed to fit to the 19" mounted posts
- Black finish

Ordering information

product code	depth	height	
JUMIU	65	45	lu
JUM7070	70	70	lu

Cage nuts



• 6mm Screws, plastic cup washers and cage nuts are supplied in packs of fifty and one hundred

description	product code
Bag of 50	CAGENUT50
Box of 100	CAGENUT100

